



MEDICAL H 710

**Impulse sealer
for medical pouches and reels
According to DIN 58953-7**

User friendly, utmost operator safety machine, dependable high quality seals, electronic control of both sealing and cooling times, independently adjustable.

The machine can be equipped with a roll holder with built in cutting device.

Safety

8 mm wide flat seal guarantees a perfect seal strength with an easy, safe and effective peelability.

Packaging

Medical H is suitable for the sealing of all known, sealable, pre-made sterile barrier systems, uncoated Tyvek[®], as well as the newest generation of packaging material.

Cleaning and Disinfection

Stainless steel top cover allows an easy and effective cleaning and disinfection.

Energy saving

All Gandus medical sealers are designed and manufactured to enable process optimization, fully respecting energy saving efficiencies.

Accessories

- Foot pedal
- Front support tray
- Roll-holder with cutting device (GT version)
-

Versions

Standard and GT version, with built-in roll holder and cutting device

MEDICAL H 710

Impulse sealer for medical pouches and reels According to DIN 58953-7

Technical data

GENERAL FEATURES

Painted Steel frame
Stainless Steel AISI 304 cover
Adjustable free edge

SEALING

Impulse sealing
Kind of sealing—flat
Sealing width 8 mm
Sealing length 710 mm
Distance sealing-medical product mm ≥ 30 Din rules

HEAT SEALABLE MATERIALS

Pouches/reels EN 868-5
Paper pouches EN 868-4
Gusseted pouches/reels
Laminated AL pouches

PP pouches
Header bags
Polyethylene

ISO 11607-2

Time control

PARAMETERS

Sealing time (sec.)

Technical data

CERTIFICATIONS/SAFETY

UNI EN 868-5:2009
DIN 58953-7
Directives 2006/42/EC—2014/30/EU-2014/35/EU
Manufactured in a UNI EN ISO 9001:2015 quality system certified company

FUNCTIONS

Microprocessor
Time setting
Energy saving

POWER SUPPLY

Power supply 100; 110/115; 230/240 VAC single phase
Multi frequency; Frequency 50/60 Hz
Max Power 2100 W

ACCESSORIES

Front Support Tray
Roll holder (GT version)
Feet pedal

SERVICES

Seal strength test EN 868-5
Maintenance

DIMENSIONS / WEIGHTS

Dimensions 710x360x220 mm / Weight 40 Kg

