

## SI 520 Med

### ISO 11607.2 fully Validatable pneumatic impulse sealer for medical pouches and reels.

#### **Packaging Process Validation**

Highest world technology used for temperature controller of impulse sealers ensures the most accurate temperature control.

Fully complying with ISO 11607-2 standard and international guidelines EN-ISO TS 16775.

#### **Safety**

8 mm wide flat seal guarantees a perfect seal strength with an easy, safe and effective peelability.

#### **Communication Interfaces**

A DIAG interface allows communication with a dedicated software for traceability.

#### **Traceability**

A dedicate traceability software is available for Gandus SI 520 Med.

#### **Packaging**

SI 520 Med is suitable for the sealing of all known, sealable, pre-made sterile barrier systems, uncoated Tyvek<sup>®</sup>, as well as the newest generation of packaging material.

#### **HI - Human Interface**

Digital display 20 characters, 4 lines and easy to use software allows a user friendly approach to our sealer.

#### **Cleaning and Disinfection**

Fully stainless steel, it allows an easy and effective cleaning and disinfection.

#### **Energy saving**

All Gandus medical sealers are designed and manufactured to enable process optimization, fully respecting energy saving efficiencies.

#### **Versions**

Also available 720 and 1020 versions.



## SI 520 Med

### ISO 11607.2 fully Validatable pneumatic impulse sealer for medical pouches and reels.

Technical data
<b>GENERAL FEATURES</b>
Stainless Steel frame
Pneumatic functioning
Impulse seal
<b>SEALING</b>
Impulse sealing
Kind of sealing—flat
Sealing width 8 mm
Sealing length 520 mm
Distance sealing-medical product mm $\geq 30$ Din rules
<b>HEAT SEALABLE MATERIALS</b>
Pouches/reels EN 868-5
Tyvek <sup>®</sup> pouches/reels
Paper pouches EN 868-4
Gusseted pouches/reels
Laminated AL pouches
PP pouches
Header bags
Polyethylene
Ultra <sup>®</sup> pouches/reels
<b>ISO 11607-2</b>
Automatic critical sealing parameters control
Temperature. Force, time control
Sealing parameters visualization and recording
Sealer functioning diagnostic and check
Alarm/stop temperature tolerance $\pm 5$ °C (DIN 58953-7)
Alarm and stop adjustable tolerance
Force alarm and stop
Time alarm and stop

Technical data
<b>CERTIFICATIONS/SAFETY</b>
UNI EN ISO 11607-2:2006
UNI EN 868-5:2009
DIN 58953-7
Directives 2006/42/EC—2014/30/EU-2014/35/EU
UNI/TR 11408:2011
Manufactured in a UNI EN ISO 9001:2015 quality system certified company
<b>PARAMETERS</b>
Sealing time (sec.)
Max sealing temperature 200°C
Reference Sealing force about 650N
Temperature tolerance $\pm 1\%$
Force Range 700-850 N
<b>CALIBRATION</b>
Heating autocalibration function
Automatic self check of thermocouple battery and remote server condition at start-up
Temperature/Force/Time calibration
<b>FUNCTIONS</b>
Microprocessor
Multilanguage menu
Temperature and time setting
Energy saving
On board battery for data retention even with machine off
Peripherals condition and diagnostic check up at start-up
Display shutdown
Settable counter
Clock and calendar function

## SI 520 Med

**ISO 11607.2 fully Validatable pneumatic impulse sealer  
 for medical pouches and reels.**

### Technical data

#### INTERFACES

Display 4 lines 20 cht

Membrane keyboard

PC connection

Remote control

DIAG port

Back up recording on PC

#### TRACEABILITY AND SOFTWARE

Traceability through DIAG interface

Ropex Visualization Remote Connection Software

#### POWER SUPPLY

Power supply 100; 110/115; 230/240 VAC single phase

Multi frequency; Frequency 50/60 Hz

Max Power 2500 W

### Technical data

#### ACCESSORIES

SIS Stand (adjustable in height)

SIPO/SIPI Working table (horizontal or inclined)

SICO Constant heat seal

SICU Cutting device max mm 450

#### SERVICES

Seal strength test EN 868-5

Machine calibration

Maintenance

#### DIMENSIONS / WEIGHTS

Dimensions 590x487x241 mm / Weight 34 Kg